

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application. Added text is indicated by underlining, deleted text is indicated by ~~strike through~~. Changes are identified by a change bar at the left edge of text.

**Listing of Claims:**

- 1                   1.       (previously presented) A system for enabling queries to a database to be  
2 processed comprising:  
3                   a database system;  
4                   an application system for providing SQL database queries to the database system,  
5 the database system coupled to the application system via a first connection over a network;  
6                   a storage system having a shared volume to store results from SQL database  
7 queries made to the database system;  
8                   a first data path to provide a data connection between the storage system and the  
9 application system, wherein the application system can directly access query results on the  
10 storage system without communicating via the first connection;  
11                  a second data path to provide a data connection between the storage system and  
12 the database system, wherein the database system directly stores query results to the storage  
13 system via the second data path without communicating via the first connection; and  
14                  a return path selector coupled to the database system for selecting a return path  
15 over which to return the results from queries made to the database system, the return path  
16 selector selecting from among at least the first connection over the network or the first data path  
17 between the storage system and the application system, wherein the return path selector  
18 determines a data path based upon one or more attributes of the query results;  
19                  wherein, when the return path is chosen to be the storage system, the results are  
20 sent to the storage system as a file and an address in the storage system for the file is provided to  
21 the application system using the first connection; and

22                    wherein the file has associated therewith a key and the key is used to control  
23                    access to the results, and also has associated therewith a flag to indicate status of the file, and  
24                    wherein the flag indicates at least one of whether the file is being written, is ready to be read, is  
25                    being read, and is available to be deleted.

1                    2.        (previously presented) A system as in claim 1 further comprising a  
2                    request path selector coupled to the application system for selecting a request path over which to  
3                    send query data comprising the SQL database queries made to the database system, the request  
4                    path selector selecting from among at least the first connection or the storage system, wherein the  
5                    key and flag are stored in the storage system.

1                    3.        (original) A system as in claim 1 wherein the storage system is coupled to  
2                    each of the application system and the database system using a switch.

1                    4.        (original) A system as in claim 3 wherein a database hub system is used  
2                    to couple the application system and the database system.

1                    5.        (previously presented) A system as in claim 1 wherein the results from  
2                    the query have a size, and the return path selector chooses a return path based on the size of the  
3                    results, and wherein said return selector compares the size of the results to a threshold to choose  
4                    said result path, and said threshold is set based on a current workload of the LAN.

1                    6.        (previously presented) A system as in claim 5 wherein the return path  
2                    selector chooses a return path based on a prediction of the size of the results, and wherein said  
3                    prediction is based on similar queries from a query execution history.

1                    7.        (original) A system as in claim 1 wherein the return path selector chooses  
2                    a return path based on a measurement of throughput of the first connection.

1                    8.        (canceled)

1                   9.       (original) A system as in claim 1 wherein after the results are used by the  
2 application system, the application system designates the results as used, thereby enabling them  
3 to be erased from the storage system at a later time.

1                   10.       (original) A system as in claim 1 wherein after the query data is used by  
2 the database system, the database system reuses the query data for a further query.

1                   11.       (canceled)

1                   12.       (canceled)

1                   13.       (canceled)

1                   14.       (previously presented) A system as in claim 10 wherein after the query  
2 data is used by the database system, the database system designates the query data as used,  
3 thereby enabling them to be erased from the storage system at a later time.

15.       (canceled)

1                   16.       (previously presented) A system as in claim 1 further comprising a hub  
2 system coupled to each of the application system and the database system.

1                   17.       (previously presented) A system for enabling queries to a database to be  
2 processed comprising:

3                   a database system;

4                   an application system for providing SQL database queries to the database system  
5 coupled to the application system via a first connection over a network;

6                   a storage system having a volume to store results from SQL database queries  
7 made to the database system;

8 a first data path to provide a data connection between the storage system and the  
9 application system, wherein the application system can directly access query results on the  
10 storage system without communicating via the first connection;

11 a second data path to provide a data connection between the storage system and  
12 the database system, wherein the database system directly stores query results to the storage  
13 system via the second data path without communicating via the first connection; and

14 a request path selector coupled to the application system for selecting a request  
15 path over which to send query data comprising the SQL database queries made to the database  
16 system, the request path selector selecting from among at least the first connection over the  
17 network or the first data path between the storage system and the application system, wherein the  
18 request path selector determines a data path based upon one or more attributes of the query data;

19 wherein, when the request path is chosen to be the storage system, the query data  
20 are sent to the storage system as a file and an address in the storage system for the file is  
21 provided to the database system using the first connection; and

22 wherein the file has associated therewith a key and the key is used to control  
23 access to the results, and also has associated therewith a flag to indicate status of the file, and the  
24 flag indicates at least one of whether the file is being written, is ready to be read, is being read,  
25 and is available to be deleted.

1 18. (original) A system as in claim 17 wherein the storage system is coupled  
2 to each of the application system and the database system using a switch.

1 19. (original) A system as in claim 18 wherein a database hub system is used  
2 to couple the application system and the database system.

1 20. (previously presented) A system as in claim 17 wherein the query data  
2 have a size, and the request path selector chooses a request path based on the size of the query  
3 data, and wherein if there is not enough space in said storage system, garbage collection is  
4 performed before storing said query data to said storage system.

1                   21.     (canceled)

1                   22.     (canceled)

1                   23.     (canceled)

1                   24.     (canceled)

1                   25.     (original) A system as in claim 17 further comprising a return path  
2 selector coupled to the database system for selecting a return path over which to return results  
3 from queries made to the database system, the return path selector selecting from among at least  
4 the first connection or the storage system.

1                   26.     (previously presented) A system as in claim 25 wherein the results from  
2 the query have a size, and the return path selector chooses a return path based on the size of the  
3 results, and wherein if there is not enough space in said storage system, garbage collection is  
4 performed before storing said query data to said storage system.

1                   27.     (previously presented) A system as in claim 17 wherein when the return  
2 path is chosen to be the storage system, the results are sent to the storage system as a file and an  
3 address in the storage system for the file is provided to the application system using the first  
4 connection.

1                   28.     (previously presented) A system for enabling queries to a database to be  
2 processed comprising:  
3                   a database system;  
4                   an application system for providing SQL database queries to the database system  
5 coupled to the application system via a first connection over a network, the application system  
6 including a database access system, and the database system including a gateway system;  
7                   a storage system having a shared volume to store results from SQL database  
8 queries made to the database system;

9 a first data path to provide a data connection between the storage system and the  
10 application system, wherein the application system can directly access query results on the  
11 storage system without communicating via the first connection;

12 a second data path to provide a data connection between the storage system and  
13 the database system, wherein the database system directly stores query results to the storage  
14 system via the second data path without communicating via the first connection; and

15 the gateway system including a return path selector for selecting a return path  
16 over which to return the results from queries made to the database system, the return path  
17 selector selecting from among at least the first connection over the network or the first data path  
18 between the storage system and the application system, wherein the return path selector  
19 determines a data path based upon one or more attributes of the query results;

20 wherein, when the request path is chosen to be the storage system, the query data  
21 are sent to the storage system as a file and an address in the storage system for the file is  
22 provided to the database system using the first connection; and

23 wherein the file has associated therewith a key and the key is used to control  
24 access to the results, and also has associated therewith a flag to indicate status of the file, and the  
25 flag indicates at least one of whether the file is being written, is ready to be read, is being read,  
26 and is available to be deleted.

1 29. (previously presented) A system as in claim 28 wherein the gateway  
2 system includes a request path selector for selecting a request path over which to send query data  
3 comprising the SQL database queries made to the database system, the request path selector  
4 selecting from among at least the first connection or the storage system.

1 30. (previously presented) A system for enabling queries to a database to be  
2 processed comprising:

3 a database system;

4 an application system for providing SQL database queries to the database system  
5 coupled to the application system via a first connection over a network, the application system  
6 including a database access system, and the database system including a gateway system;

7 a storage system having a volume to store results from SQL database queries  
8 made to the database system;

9 a first data path to provide a data connection between the storage system and the  
10 application system, wherein the application system can directly access query results on the  
11 storage system without communicating via the first connection;

12 a second data path to provide a data connection between the storage system and  
13 the database system, wherein the database system directly stores query results to the storage  
14 system via the second data path without communicating via the first connection; and

15 the database access system including a request path selector for selecting a request  
16 path over which to send data comprising the SQL database queries made to the database system,  
17 the request path selector selecting from among at least the first connection over the network or  
18 the first data path between the application system and the storage system;

19 wherein, when the request path is chosen to be the storage system, the query data  
20 are sent to the storage system as a file and an address in the storage system for the file is  
21 provided to the database system using the first connection; and

22 wherein the file has associated therewith a key and the key is used to control  
23 access to the results, and also has associated therewith a flag to indicate status of the file, and the  
24 flag indicates at least one of whether the file is being written, is ready to be read, is being read,  
25 and is available to be deleted.

1 31. (currently amended) A system for enabling queries to a database to be  
2 processed comprising:

3 a database system;

4 an application system for providing SQL database queries to the database system,  
5 the database system coupled to the application system via a communications network  
6 connection;

7 a switch coupled to each of the database system and the application system;  
8 a storage system coupled to the switch, the storage system having a volume to  
9 store results from SQL database queries made to the database system;  
10 a first data path to provide a data connection between the storage system and the  
11 application system, wherein the application system can directly access query results on the  
12 storage system without communicating via the first connection;  
13 a second data path to provide a data connection between the storage system and  
14 the database system, wherein the database system directly stores query results to the storage  
15 system via the second data path without communicating via the first connection; and  
16 a return path selector coupled to the database system for selecting a return path  
17 over which to return the results from queries made to the database system, the return path  
18 selector selecting from among at least the ~~first connection over the network communications~~  
19 network connection or the first data path between the storage system and the application system,  
20 wherein the return path selector ~~determines a data path~~ selects a return path based upon one or  
21 more attributes of the query results;  
22 wherein when the return path is selected to be the storage system, the results are  
23 sent to the storage system as a file and an address in the storage system for the file is provided to  
24 the database system using the communications network connection;  
25 wherein the database system is configured to generate a key associated with the  
26 file for the results to identify their location, send the key over the network to the ~~query~~  
27 ~~provider~~ application, and encrypt at least one of the key and the results;  
28 wherein the key is used to control access to the results, and also has associated  
29 therewith a flag to indicate status of the file, and wherein the flag indicates at least one of  
30 whether the file is being written, is ready to be read, is being read, and is available to be deleted.

1 32. (previously presented) A system as in claim 31 further comprising a  
2 request path selector coupled to the application system for selecting a request path over which to  
3 send query data comprising the SQL database queries made to the database system, the request  
4 path selector selecting from among at least the communications network connection or the



switch, and wherein said return selector compares the size of the results to a threshold to choose said result path, and said threshold is set based on a current workload of the LAN.

33. (currently amended) A method of returning results to a query provider, in the method for use in a system having a query provider which provides SQL database queries to a database system connected to the query provider by a first connection over a network, the query provider and the database system being each coupled to a storage system via different paths, a method of returning results to the query provider, a the method comprising:

selecting a second connection, comprising a path from the query provider to the storage system, for storing results from SQL database queries made to the database system in the storage system as a file at an address which can be accessed separately by the query provider via a the second connection independent of the network and by the database system via a third connection independent of the network, comprising a path from the database system to the storage system; and

sending the address of the results in the storage system via the first connection over the network to the query provider;

generating a key for the results to identify their location, wherein the key is used to control access to the results, and also has associated therewith a flag to indicate status of the file, and wherein the flag indicates at least one of whether the file is being written, is ready to be read, is being read, and is available to be deleted; and

sending the key over the network to the query provider.

34. (canceled).

35. (currently amended) A method as in claim 34-33 further comprising a step of, at the query provider, retrieving the results from the storage system.

36. (currently amended) A method as in claim 34-33 further comprising encrypting at least one of the key and the results.

1           37.     (previously presented) A method as in claim 33 wherein the query  
2 provider provides query data comprising the SQL database queries to the database by storing the  
3 query data in the storage system at a location and sending information about the location over the  
4 first connection to the database system.

1           38.     (previously presented) A method as in claim 33 further comprising, at the  
2 database system, the steps of:  
3                 retrieving the query data from the storage system; and  
4                 using the query data to obtain the results.

1           39.     (original) A method as in claim 33 further comprising providing a flag  
2 associated with the results to indicate whether the results are ready to be read by the query  
3 provider.

1           40.     (original) A method as in claim 37 further comprising providing a flag  
2 associated with the results to indicate whether the results have been read by the query provider.

1           41.     (currently amended) A method for use in~~In~~ a data storage system  
2 connected to an application system and a database system via a network, ~~a~~the method  
3 comprising:  
4                 receiving from the database system over the network, results of execution of SQL  
5 database queries, the SQL database queries being sent to the database system by the application  
6 system;  
7                 storing the results of execution of SQL database queries in a storage area that the  
8 database system and the application system can access separately via separate connections to the  
9 storage area, the separate connections comprising:  
10                a first data path to provide a data connection between the storage system  
11 and the application system, wherein the application system can directly access query results on  
12 the storage system without communicating via the first connection; and

13 a second data path to provide a data connection between the storage  
14 system and the database system, wherein the database system directly stores query results to the  
15 storage system via the second data path without communicating via the first connection;

16 determining a return path for the results of the execution of queries to the  
17 application system based upon one or more attributes of the results of the execution of queries;  
18 and

19 sending, in response to a request from the application system, the results of  
20 execution of queries to the application system over the network if the network is determined to  
21 be the return path or returning an address in the shared volume for the results of the execution of  
22 the query if the shared volume is determined to be the return path;

23 the method further comprising:  
24 generating a key for the results to identify their location, wherein the key is used  
25 to control access to the results, and also has associated therewith a flag to indicate status of the  
26 file, and wherein the flag indicates at least one of whether the file is being written, is ready to be  
27 read, is being read, and is available to be deleted;

28 sending the key over the network to the query provider; and  
29 encrypting at least one of the key and the results.

1 42. (currently amended) A method comprising: In a system having an  
2 application system, a database system connected to the application system via a first network  
3 connection, a return path selector coupled to the database system for selecting a return path over  
4 which to return the results from queries made to the database system, and a data storage system  
5 connected to the application system via a first data path and connected to the database system  
6 through a second data path, the first data path providing a data connection between the data  
7 storage system and the application system through which the application system can directly  
8 access query results on the data storage system without communicating via the first connection,  
9 and the second data path providing a data connection between the data storage system and the  
10 database system through which the database system directly stores query results to the data

~~storage system via the second data path without communicating via the first connection, a method, comprising the steps of:~~

~~sending an SQL database query, in a system having an application system, a database system connected to the application system via a first network connection, a return path selector coupled to the database system for selecting a return path over which to return the results from queries made to the database system, and a data storage system connected to the application system via a first data path and connected to the database system through a second data path, the first data path providing a data connection between the data storage system and the application system through which the application system can directly access query results on the data storage system without communicating via the first connection, and the second data path providing a data connection between the data storage system and the database system through which the database system directly stores query results to the data storage system via the second data path without communicating via the first connection, from the application system to the database system by using the first network connection;~~

    selecting a return path over which to return the results from SQL database queries made to the database system from among at least the first network connection or the first data path between the storage system and the application system, wherein the return path selector determines the return path based upon one or more attributes of the query results;

    storing a result of execution of the query in a shared volume of the data storage system that can be accessed by the application system via the first data path and by the database system via the second data path; and

    obtaining at the application system, the result of execution of the query from the storage system via the first data path without going through the first connection over the network;

the method further comprising:

    generating a key for the results to identify their location, wherein the key is used to control access to the results, and also has associated therewith a flag to indicate status of the

38 | file, and wherein the flag indicates at least one of whether the file is being written, is ready to be  
39 | read, is being read, and is available to be deleted;

40 |                   sending the key over the network to the query provider; and  
41 |                   encrypting at least one of the key and the results.

1                   43.     (original) The method of claim 42, wherein the first connection is a Local  
2     Area Network, and wherein the second connection is a Storage Area Network.